Safety data sheet

Condor Fix Remover spray

revision of: 19/01/2005 version number: 001

1. Identification of the substance	/ preparation an	d the compa	ny / undertaking	
1.1 Identification of the substance or preparation			Condor Fix Remover spray	
1.2. Use of the substance / preparation			Accessories for photography and professional studios	
1.3. Company / undertaking identification			Condor Foto s.a.s. – via Prinetti 32 20127 Milano tel. 0039 02 2611 0946 - fax 0039 02 2614 7831	
1.4. Emergency telephone			tel. 0039 02 2611 09	946
2. Composition / Information on in	ngredients			
2.1. Hazardous components				
Substance	concentration (CAS number	Einecs	Risk phrases (*):
propane	5-10%	74-98-6		R13
butane	10-20%	106-97-8		R13
n-butyl acetate	30-50%	123-86-4		R10 R66 R67
2-propanone	10-20%	67-64-1		R11
The propellent is propane-butane	for spray produ	icts.		
(*) for the complete text of risk ph	rases, see para	graph 16		
3. Hazards identification				
The product may flare up when n (over 50°C)	aked flames are	e present. Th	e spray can may exp	plode at high temperatures
4. First aid measures				
4.1. Inhalation:	Remove pa	itient to fresh	air, keep at rest.	
4.2. Eye contact:		First rinse with plenty of water for several minutes (remove contact lense easily possible), then take to a doctor. Wash with soap and water.		nutes (remove contact lenses if
4.3. Skin contact:				
4.4. Ingestion:	Rinse with	plety of wate	r. Do not induce vom	iting. Obtain medical attention.
If indisposition insist, obtain medi	cal attention.			
			page ?	1/4 - Adesivo temporaneo spray

5. Fire-fighting measures				
The product contains extremely flammable liquefied gas.				
5.10 Exstinguishing media:	carbon dioxide - dry powder - foam.			
5.20 Special procedures:	In case of fire, use protective equipment. Cool fire-exposed containers. Containers may explode.			
6. Accidental release measures				
6.1. Personal precautions:	Appropriate clothing and rubber gloves can be weared.			
6.2. Enviromental precautions:	Do not allow to enter water courses. Contain spillages with absorbent material. Avoid sparks and naked flames. Stop engines. Do not smoke.			
6.3. Methods of cleaning up:	Contain spillages with absorbent material. Sweep up with absorbent material and dispose according to local laws.			
7. Handling and storage:				
7.1. Handling	Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Do not smoke. Keep out of reach of children			
7.2. Storage7.3. Specific use(s)	(If great quantities are involved) Store out of direct sun-light in ventilated area and keep away from flames. Avoid buil-up of electrostatic charges, keep away from incandescent materials and sources of ignition. No other uses are known.			
8. Exposure controls / Personal Prot	ection			
8.1. Exposure limit values				
propane butane n-butyl acetate 2-propanone	TLV: 2500 ppm TWA; (ACGIH 2003) TLV: 800 ppm TWA; (ACGIH 2003) TLV: 150 ppm come TWA; 200 ppm come STEL; (ACGIH 2003) TLV 750 ppm; 1780 mg/m3 (ACGIH 1993-1993)			
8.2.1. Occupational exposure controls No particular protection equipment is necessary when the product is normally used. Follow general use of ventilation when spray is involved.				
8.2.1.1. Respiratory protection	Not necessary for normal use. Follow general use of ventilation when spray is involved.			
8.2.1.2. Hand protection	Not necessary for normal use.			
8.2.1.3. Eye protection	Not necessary for normal use.			
8.2.1.4. Skin protection	Not necessary for normal use.			
8.2.2. Environmental exposure controls	Not available data.			

9. Physical and chemical properties				
9.1. General information 9.1.1. Appearance		Spray cap	Colorless.	
9.1.2. Odour		Spray can. Sweet.	Coloness.	
9.2. Important health, safety and env	vironmental			
9.2.1. pH:		Not applicable.		
9.2.2. Boiling point / boiling range:		-0,5 °C		
9.2.3. Flash point:		-60 °C		
9.2.4. Flammability (solid, gas);		287 °C		
9.2.5. Explosive properties		Not available data.		
9.2.6. Oxydising properties		Not available data.		
9.2.7. Relative density:		Not available data.		
9.2.8 Solubility:				
9.2.8.1. Water solubility:		Incomplete.		
9.2.8.2. Fat solubility:		Incomplete.		
9.2.9. Partition coeff.: n-octanol /wat	er:	Not available data.		
9.2.10. Viscosity:		Not available data.		
9.2.11. Vapour density:		Not available data.		
9.2.12. Evaporation rate: 9.3. Other information		Not available data. Pressure: 3,5 bar at	20°C - 8 bar at 50°C	
		Flessure. 5,5 bar at	20 C - 6 Dai al 50 C	
10. Stability and ractivity				
The product is stable . No hazardous	chemicals	are known to be form	ned during conventional uses of it.	
10.1. Conditions to avoid			n ventilated area and keep away from escent materials and sources of ignition.	
10.2. Materials to avoid	None.			
10.3. Hazardous decomposition products	None.			
11. Toxicological information				
This product has not been tested for toxicity. In case, see at single components' safety data sheets. Propellent does not present chemical hazard for skin and mucosae.				
12. Ecological information:				
12.1. Ecotoxicity	Not availa	ble data.		
12.2. Mobility	Not availa	ble data.		
12.3. Persistence and degradability	Not availa	ble data.		
12.4. Bioaccumulative potential	Not availa	ble data.		
12.5. Other adverse effects	Not availa	ble data.		
			nogo 2/4 Adapiya tamparanag arrest	
			page 3/4 - Adesivo temporaneo spray	

13. Disposal considerations:

Residues and empty containers must not be allowed to enter drains and water courses. Follow local environmental laws.

14. Transport information

UN number	1950
ADR (road)	classe 2 - lettera 5°F
RID (rail)	classe 2 - lettera 5°F
IMDG (sea)	classe 2 - pagina 2102 - gruppo di imballaggio aerosol
ICAO / IATA (air)	classe 2.1

15. Regulatory information

In accordance with EC directive, (91/155/CE, 2001/58/CE, 94/1/CE, 2004/73/CE), the product is labelled:

Classification: Extremely Flammable.

Risk phrases	R12 R66 R67	Extremely flammable Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.
Safety advice	S9 S16 S15	Keep container in a well-ventilated place Keep away from sources of ignition-No smoking Keep away from heat

Keep out of reach of children

S2

1	6.	(Dther	information	

Risk phrases (paragraph 2)

- R13 Extremely flammable liquefied gas
- R10 Flammable
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.
- R11 Highly flammable

Bibliography: NIOSH - Registry of toxic effects of chemical substances.

I.SAX-Dangerous properties of industrial materials.

The information of this safety data sheet is based on our present knowledges.

This safety data sheet conforms to EC 91/155/EC, 2001/58/EC, 2001/59/EC, 2004/73/EC

Since the condition of handling and use are beyond our control, we make no guarantee of results. We assume no liability for damages resulting from following our suggestions or reccomendations.

This safety data sheet sustitutes all previous edition - previous edition number: Revised section: All section revised.