Safety data sheet

Eco Magnodust spray

revision of: 19/01/2005 version number: 001

1. Identification of the substance / p	preparation and	d the compa	ny / undertaking		
1.1 Identification of the substance or preparation			Eco Magnodust spray		
1.2. Use of the substance / preparation1.3. Company / undertaking identification			Accessories for photography and professional studios Condor Foto s.a.s. – via Prinetti 32 20127 Milano tel. 0039 02 2611 0946 - fax 0039 02 2614 7831		
1.4. Emergency telephone			tel. 0039 02 2611 0946		
2. Composition / Information on ing	redients				
2.1. Hazardous components					
Substance c	oncentration C	CAS number	Einecs	Risk phrases (*):	
propane butane 2-propanol	5-10% 10-20% 50-75%	74-98-6 106-97-8 67-63-0		R13 R13 R11 R36 R67	
The propellent is propane-butane for spray products.					
(*) for the complete text of risk phrases, see paragraph 16					
3. Hazards identification					
The product may flare up when naked flames are present. The spray can may explode at high temperatures (over 50°C)					
4. First aid measures					
4.1. Inhalation:	Remove pa	tient to fresh	air, keep at rest.		
4.2. Eye contact:		First rinse with plenty of water for several minutes (remove contact lenses if			
4.3. Skin contact:	• •	easily possible), then take to a doctor. Wash with soap and water.			
4.4. Ingestion:	Rinse with p	olety of wate	r. Do not induce vomi	ting. Obtain medical attention.	
If indisposition insist, obtain medical attention.					
			sa	age 1/4 - Eco Magnodust spray	

5. Fire-fighting measures				
The product contains extremely flammable liquefied gas.				
5.10 Exstinguishing media:	carbon dioxide - dry powder - foam.			
5.20 Special procedures:	In case of fire, use protective equipment. Cool fire-exposed containers. Containers may explode.			
6. Accidental release measures				
6.1. Personal precautions:	Appropriate clothing and rubber gloves can be weared.			
6.2. Enviromental precautions:	Do not allow to enter water courses. Contain spillages with absorbent material. Avoid sparks and naked flames. Stop engines. Do not smoke.			
6.3. Methods of cleaning up:	Contain spillages with absorbent material. Sweep up with absorbent material and dispose according to local laws.			
7. Handling and storage:				
7.1. Handling	Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Do not smoke. Keep out of reach of children			
7.2. Storage 7.3. Specific use(s)	(If great quantities are involved) Store out of direct sun-light in ventilated area and keep away from flames. Avoid buil-up of electrostatic charges, keep away from incandescent materials and sources of ignition. No other uses are known.			
8. Exposure controls / Personal Prot	ection			
8.1. Exposure limit values				
propane butane 2-propanol	TLV: 2500 ppm TWA; (ACGIH 2003) TLV: 800 ppm TWA; (ACGIH 2003) TLV: 400 ppm (come TWA); 500 ppm (come STEL) (ACGIH 1998).			
8.2.1. Occupational exposure controls No particular protection equipment is necessary when the product is normally used. Follow general use of				
ventilation when spray is involved. 8.2.1.1. Respiratory protection	Not necessary for normal use. Follow general use of ventilation when spray is involved.			
8.2.1.2. Hand protection	Not necessary for normal use.			
8.2.1.3. Eye protection	Not necessary for normal use.			
8.2.1.4. Skin protection	Not necessary for normal use.			
8.2.2. Environmental exposure controls	Not available data.			

9. Physical and chemical properties				
9.1. General information		0		
9.1.1. Appearance 9.1.2. Odour		Spray can. Sweet.	Colorless.	
9.2. Important health, safety and env	vironmental			
9.2.1. pH:	nonnontai	Not applicable.		
9.2.2. Boiling point / boiling range:		-0,5 °C		
9.2.3. Flash point:		-60 °C		
9.2.4. Flammability (solid, gas);		287 °C		
9.2.5. Explosive properties		Not available data.		
9.2.6. Oxydising properties		Not available data.		
9.2.7. Relative density:		Not available data.		
9.2.8 Solubility:				
9.2.8.1. Water solubility:		Incomplete.		
9.2.8.2. Fat solubility:		Incomplete.		
9.2.9. Partition coeff.: n-octanol /wate	er:	Not available data.		
9.2.10. Viscosity:		Not available data.		
9.2.11. Vapour density: 9.2.12. Evaporation rate:		Not available data. Not available data.		
9.3. Other information		Pressure: 3,5 bar at	20°C - 8 bar at 50°C	
10. Stability and ractivity				
The product is stable. No becordous	abamiaala	are known to be form	and during conventional upon of it	
The product is stable . No hazardous				
10.1. Conditions to avoid			n ventilated area and keep away from escent materials and sources of ignition.	
10.2. Materials to avoid	None.			
10.3. Hazardous decomposition products	None.			
11. Toxicological information				
This product has not been tested for toxicity. In case, see at single components' safety data sheets. Propellent does not present chemical hazard for skin and mucosae.				
12. Ecological information:				
12.1. Ecotoxicity	Not availa	ble data.		
	Not ovell-	bla data		
12.2. Mobility	Not availa			
12.3. Persistence and degradability	Not availa	ble data.		
12.4. Bioaccumulative potential	Not availa	ble data.		
12.5. Other adverse effects	Not availa	ble data.		
			page 3/4 - Eco Magnodust spray	

13. Disposal considerations:

Residues and empty containers must not be allowed to enter drains and water courses. Follow local environmental laws.

14. Transport information

UN number	1950
ADR (road)	classe 2 - lettera 5°F
RID (rail)	classe 2 - lettera 5°F
IMDG (sea)	classe 2 - pagina 2102 - gruppo di imballaggio aerosol
ICAO / IATA (air)	classe 2.1

15. Regulatory information

In accordance with EC directive, (91/155/CE, 2001/58/CE, 94/1/CE, 2004/73/CE), the product is labelled:

Classification: Extremely Flammable.

Risk phrases	R12 R66 R67	Extremely flammable Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.
Safety	S9	Keep container in a well-ventilated place
advice	S16	Keep away from sources of ignition-No smoking
	S15	Keep away from heat
	S2	Keep out of reach of children

16. Other information

Risk phrases (paragraph 2)

- R13 Extremely flammable liquefied gas
- R11 Highly flammable
- R36 Irritating to eyes
- R67 Vapours may cause drowsiness and dizziness.

Bibliography: NIOSH - Registry of toxic effects of chemical substances.

I.SAX-Dangerous properties of industrial materials.

The information of this safety data sheet is based on our present knowledges.

This safety data sheet conforms to EC 91/155/EC, 2001/58/EC, 2001/59/EC, 2004/73/EC

Since the condition of handling and use are beyond our control, we make no guarantee of results. We assume no liability for damages resulting from following our suggestions or reccomendations.

This safety data sheet sustitutes all previous edition - previous edition number: Revised section: All section revised.

page 4/4 - Eco Magnodust spray